

Internal Pipe Blast Tool PBT-2 ROTOBLAST



- For pipes 12" (304,8 mm) to 36" (914,4 mm) ID
- Variable feed and optimal rotation speed offers flexibility in cleaning rates for varying surface conditions
- Adjustable centering carriage for consistent blast pattern
- Use with standard blast machine

The PBT-2 ROTOBLAST is an accessory for all Contracor blast machines that allows easy cleaning of the internal surface of steel pipes. It is durable, portable, and most of all, easy to use. It guaranteed considerable increases in productivity. The PBT-2 ROTOBLAST consists of an adjustable centre carriage and a constant speed rotating blast head to produce a uniform cleaned blast surface. The carriage is infinitely adjustable from 12" (304,8mm) to 36" (914,4mm) inside diameter. The rotating head is driven by compressed air and two radially positioned blast nozzles. The adjustment of the feed allows a high operational flexibility with all degrees of corrosion of the inner surfaces. The PBT-2 ROTOBLAST unit can be operated with nozzle sizes from 5.0mm to 9.5mm inner diameter.

Standard delivery

Three leg sets, 2 x NTC(F)-5.0 nozzles, 10 x spare leather washers.

Order code	Model	Description
12730	PBT-2 ROTOBLAST	Pipe blasting tool 12" (304,8mm) - 36" (914,4mm). Complete package incl. three leg sets, 2 x NTC(F)-5.0 nozzles, 10 x spare leather washers
29003024	NTC(F)-5.0	Dia. 5.0 mm TC Blast nozzle for PBT-2 ROTOBLAST
29003025	NTC(F)-6.5	Dia. 6.5 mm TC Blast nozzle for PBT-2 ROTOBLAST
29003026	NTC(F)-8.0	Dia. 8.0 mm TC Blast nozzle for PBT-2 ROTOBLAST
29003027	NTC(F)-9.5	Dia. 9.5mm TC Blast nozzle for PBT-2 ROTOBLAST