



PRODUCT DATA SHEET
AWL®WASH Wash Down Concentrate 73234

Features & Uses

Formulated to clean AWLGRIP®, AWLCRAFT® 2000, and AWLGRIP 2 Topcoats. Awlwash does not contain alkalis, acids, or abrasives. It is free rinsing, which decreases drying time, and is 100% biodegradable.

Awlwash contains no materials harmful to the Marine Environment as defined in 'Annex III of the Dangerous Substances Directive 67/548/EEC' and can be discharged with wash water within the provisions of MARPOL Annex V [Resolution MEPC.201(62)].

Specification Data

Type: Wash Down Concentrate
Packaging: Quarts (.946 Liters) and Gallons (3.785 Liters), Quart (.946 Liters) is a refillable "tip 'n measure" container.
Theoretical Coverage: 1 oz. (30 ml) of AWLWASH® per Gallon of Water

VOC: 0 g/lit or 0 lbs/gallon

Keep container tightly closed and upright to prevent leakage.
Keep from freezing.

Product Components, Reducers, Additives, and Auxiliary Components

AWLWASH.....73234

Application Equipment

Use a soft, non-abrasive applicator.

Surface Preparation

Rinse surface thoroughly prior to washing.

Mixing & Reduction

One (1) ounce (30 ml) of AWLWASH per each gallon (3.785 Liters) of water.

Application Instructions

Wash surface while still wet from initial rinsing, using a soft, non-abrasive applicator when washing the surface. Do not allow AWLWASH to dry on the surface prior to rinsing. Wash small sections of large surfaces to insure the surface stays wet. Rinse thoroughly after washing. When finished, wipe surface with soft cotton towel or chamois to prevent water spots.

Note: If water spots are a problem, Awlgrip recommends the use of a water softener to reduce water spots. Water spots are caused by organic and inorganic impurities in the water. If water beads are allowed to air dry, the water evaporates and leaves a residue on the paint. If this residue is not removed it may gradually etch the paint. If water spots occur, they can be removed with Awlgrip's AWL®CARE Protective Polymer Sealer (73240).

Stubborn stains may require a higher concentration of AWLWASH. High concentrations will require increased amounts of rinsing. Some stubborn stains may require AWLWASH to be used at full strength.

2270 Morris Ave • Union • New Jersey 07083 • USA • Tel: 908.686.1300 • Fax: 908.964.2219
Bannerlaan 54 • B-2280 Grobbendonk • Belgium • Intl. Tel: 32.14.257770 • Intl. Fax: 32.14.230880
76 Waterway Drive • Coomera • QLD 4209 • Australia • Tel: 61.7.5573.9655 or 1800.007.866 • Fax: 61.7.5573.9677
686 Rosebank Road • Avondale • Auckland • New Zealand • Tel: 64.9.828.3009 • Fax: 64.9.828.1129
3 Neythall Road • Singapore 628570 • Tel: 65.6862.2928 • Fax: 65.6862.0778



PRODUCT DATA SHEET AWL®WASH Wash Down Concentrate 73234

Note: Awlgrip recommends washing the surface once a week to prevent dirt build up.

Please reference Awlgrip's website: www.awlgrip.com for further information regarding care and maintenance of Awlgrip products.

Warning:

Temperature Range: Optimal Surface/Ambient Temperature range is 18°C (60°F) to 35°C (95°F). Proper Application and/or cure results may be more difficult to achieve when conditions are outside this range. Do not apply paint materials to surfaces less than 3°C or 5° F above dew point. Do not apply paint materials to surfaces warmer than 41°C (105°F). Ambient temperature should be minimum 10°C (50°F) and maximum 41°C (105°F).

The information in this Product Data Sheet is not intended to be exhaustive. Any person using the product without first making further enquiries as to the suitability of the product for the intended purpose does so at their own risk and, to the extent permitted by law, we can accept no responsibility for the performance of the product or for any loss or damage arising out of such use. The information contained in this Product Data Sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Awlgrip® and all products mentioned in this Product Data Sheet are trademarks of, or licensed to, AkzoNobel.

© AkzoNobel, 2013

2270 Morris Ave • Union • New Jersey 07083 • USA • Tel: 908.686.1300 • Fax: 908.964.2219
Bannerlaan 54 • B-2280 Grobbendonk • Belgium • Intl. Tel: 32.14.257770 • Intl. Fax: 32.14.230880
76 Waterway Drive • Coomera • QLD 4209 • Australia • Tel: 61.7.5573.9655 or 1800.007.866 • Fax: 61.7.5573.9677
686 Rosebank Road • Avondale • Auckland • New Zealand • Tel: 64.9.828.3009 • Fax: 64.9.828.1129
3 Neythall Road • Singapore 628570 • Tel: 65.6862.2928 • Fax: 65.6862.0778