



Fussy Filla

Description

Fussy Filla is a ready to use water-based filler suitable for small and medium-sized holes / cavities. Is able to used interior and exterior applications

Product Information

Packaging	Size
Tube	200 ML
Pail	1 LITRE
Pail	4 LITRE

Uses

Suitable for use on timber, brick, plasterboard and fibre cement

Features

- Long Lasting
- Paintable
- Interior and Exterior applications
- Low Shrink

Technical Details

Property	Typical Result
Technology	Water-based
Colour	Light Green
Density	1.02 to 1.05
Shelf Life (un-opened cartridge)	12 Months

Indicative data only, not intended for preparation of specifications

Directions for Use

1. Ensure surfaces are clean, dry and free from dust or grease.
2. Prime the surface before application for best results.
3. Apply the filler with flexible filling blade by pressing and pushing the filler firmly into a hole/cavity (do not underfill to avoid filler sagging).
4. Apply additional fill if required for larger holes/ cavities.
5. Allow the first layer to dry before the second fill application.
6. Allow the filler to dry completely before fine sanding. Ensure surface is clean and dust free before painting.

Clean up:

- Uncured product may be removed with water.
- Cured product can be removed by sanding and scraping.
- Tools can be washed with soapy water

Storage

For maximum shelf life, the product should be kept sealed and in a cool, place out of direct sunlight. Store product above 5 °C

Limitations

- Do not apply or store below 5 °C.
- Not suitable for permanent water immersion or in constantly damp areas

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.tfb.tools/FillaSDS