

DURAPOS®

Point of sale hardware for professionals.

DPT-100

Thermal ticket printer

- Simple and elegant
- Easy paper loading
- 300mm/s high printing speed
- Triple interface !!
- support flat, wall-mount
- 2 years SWAP warranty
- Competitive pricing



DPT-100



Print	Printing Method	Thermal line
	Effective Printing Width	72mm or 64mm
	Resolution	203dpi (8 dot/mm)
	Printing Speed	300mm/S
	Printing Density	504dot/line or 576dot/line
	Character Set	ANK,GB18030(Chinese)
	Print Font	ASCII Font A : 12×24 ASCII Font B : 9×24 Chinese: 24×24
	Character per Line	Font A-42line or 48line/Font B-56line or 64line/Simplified、 complex font-21line or 24line
	Line space	3.75mm (available command to adjust line space)
Paper Spec	Paper Width	79.5±0.5mm
	Paper Roll Diameter	Φ80mm
	Paper supply method	easy paper loading
Barcodes	Barcodes type	UPC-A,UPC-C,EAN-13,EAN-8,CODE39,ITF, CODEBAR, CODE93, CODE128
	Extended character table	PC437, Katakana, PC850, PC860, PC863, PC865, WPC1252, PC866, PC852, PC858
Reliability	MCBF	60 million lines
	TPH	100 million pulses (100KM)
	Auto cutter	1,000,000 cuts
Interface	DPT100-URE : Serial+Ethernet+USB DPT100-URW : WIFI+Serial+USB	
Page mode	8KBytes (not page mode) / 1M (page mode)	
NV bitmap Flashd size	64KBytes	
Paper near end sensor	Yes	
Beeper	Yes	
Wallmount mounting	Yes with option DPT100-WMB	
Printing command	ESC POS / OPOS	
System supported	Windows / OPOS / Linux / Android / IOS	
Power Supply(Adapter)	DC 24V,2.5A	
Standard supplied in box	Power supply / USB cable / Serial cable / Drivers / paper roll	
Certificate	FCC、 CE、 3C	
Printer Dimesion (L x W x H)	200×145×142mm	
Weight	1.5kg	
Environment	Temperature	Operating : 0~45°C Stock : -10~50°C

