



Product Data Sheet

MOTOR OIL CP 0W-30

Product Description:

MOTOR OIL CP 0W-30 is a high performance fuel saving engine oil based on 100% synthetic and PAO technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans where a ACEA A5/B5 specification is required and suitable for all engines which require an ACEA C2 and PSA B71 2290 performance specification.

MOTOR OIL CP 0W-30 is based on high performance PAO (PolyAlphaOlefine) synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.

MOTOR OIL CP 0W-30 exceeds the following performance criteria:

API SN/CF ACEA A1/B1 ACEA A5/B5 ACEA C2
PSA B71 2290

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	0W-30
Density@15°C	kg/m ³	ASTM D4052	856
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	70
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	10,5
Viscosity Index		ASTM D2270	165
Viscosity CCS @-30°C, max	cP	ASTM D2270	6200
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	7,5
Sulphated Ash	%Wt	ASTM D874	0,79

Product Nr: 4243

Date Issued: 11-02-2015

Date Superseded:

Revision nr: 01