



Product Data Sheet

MOTOR OIL VLV 0W-20

Product Description:

Motor Oil Synth VLV 0W-20 is a fuel saving oil based on 100% synthetic technology specially designed for use in Volvo passenger cars with or without turbocharger where Volvo VCC RBS0-2AE is required.

Motor Oil Synth VLV 0W-20 is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Protection to wear by cold start.
- Very good low temperature properties.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Added fuel economy

MOTOR OIL VLV 0W-20 exceeds the following performance criteria:

Volvo VCC RBS0/2AE ACEA A1/B1 API: SN

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	0W-20
Density@15°C	kg/m ³	ASTM D4052	845
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	47,8
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9,11
Viscosity Index		ASTM D2270	172
Viscosity CCS @-30°C, max	cP	ASTM D2270	<6200
Flash Point COC	°C	ASTM D92	230
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	8,0
Sulphated Ash	%Wt	ASTM D874	0,80

Product Nr: 4244	Date Issued: 13-03-2015	Date Superseded:	Revision nr: 0
------------------	-------------------------	------------------	----------------