



Product Data Sheet

RACING OIL SL 10W-60

Product Description:

RACING OIL SL 10W-60 is a high performance fully synthetic motor oil of exceptional quality, delivering extreme performance in gasoline-, diesel- and LPG fuelled engines in passenger cars with or without turbocharger, working under severe temperature and load conditions.

RACING OIL SL 10W-60 is based on high quality 100% synthetic Poly Alpha Olefin (PAO) in combination with an unique additive package to ensure the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions.

RACING OIL SL 10W-60 exceeds the following performance criteria:

API SL ACEA A3/B4 MB 229.1 VW 502.00/505.00

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	10W-60
Density@15°C	kg/m ³	ASTM D4052	851
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	173
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	24
Viscosity Index		ASTM D2270	170
Viscosity CCS @-20°C, max	cP	ASTM D2270	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-30
Total Base Number	mgKOH/g	ASTM D2896	11.4
Sulphated Ash	%Wt	ASTM D874	1.3

Product Nr: 4201

Date Issued: 25-10-2012

Date Superseded: 29-07-2011

Revision nr: 02