



Product Data Sheet:

MOTORCYCLE OIL 2T

Product Description:

MOTORCYCLE OIL 2T is a high quality lubricant suitable for use in air cooled 2-stroke gasoline engines working under a wide variety of conditions and is formulated from highly refined mineral base stocks and fortified with carefully selected additives to provide engine protection and cleanliness in 2-stroke engines.

MOTORCYCLE OIL 2T offers excellent lubricity that protects against piston scuffing and premature wear of engine components. The low ash formulation effectively prevents pre-ignition and spark plug fouling. The excellent miscibility with gasoline ensures stable homogeneous mixtures at low ambient temperatures.

MOTORCYCLE OIL 2T is recommended for 2-stroke motorcycles and scooters requiring API TC and/or JASO FB quality oil and is suitable for both oil-injection and premix lubrication systems. Always follow manufacturer's recommendation regarding oil to fuel ratio.

Specifications:
Exceeds: API TC, JASO FB

Property:	Test Method:	Typical Values:
Density @ 15°C	ASTM D4052	883 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D7042	70 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	9.2 mm ² /s
Viscosity Index	ASTM D2270	110
Flash Point	ASTM D92	>100°C
Pour Point	ASTM D97	-30°C
Total Base Number	ASTM D2896	1.2 mgKOH/g
Sulphated Ash	ASTM D874	0.25 wt %

Product nr: 4292

Date Issued: 08/08/2011

Date Superseded: 07/07/2010

Revision nr: 01