



Product Data Sheet:

MOTORCYCLE OIL 2T EXTRA

Product Description:

MOTORCYCLE OIL 2T EXTRA is a premium quality semi-synthetic lubricant especially developed for high powered air-cooled 2-stroke gasoline engines fitted with oil-injection or premix systems and is formulated from premium quality mineral and synthetic base stocks and high quality performance additives to provide exceptional engine protection and cleanliness in 2-stroke engines.

MOTORCYCLE OIL 2T EXTRA offers excellent lubricity which protects against piston scuffing and premature wear of engine components. The low ash formulation effectively prevents pre-ignition and spark plug fouling. The excellent miscibility with gasoline ensures stable homogeneous, stable mixtures at low ambient temperatures.

MOTORCYCLE OIL 2T EXTRA exceeds the latest international specifications of JASO FD, ISO-L-EGD and API TC as well as the requirements of leading 2-stroke engine manufacturers.

MOTORCYCLE OIL 2T EXTRA is recommended for a wide range of high-powered 2-stroke motorcycles and scooters running ISO-L-EGD or JASO FD quality oils and is suitable for both oil injection and pre-mix lubrication systems.

Always follow manufacturers recommendations regarding the oil to fuel ratio!

Specifications:

Exceeds: API TC, ISO-L-EGD, JASO FD

Property:	Test Method:	Typical Values:
Density @ 15°C	ASTM D4052	883 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D7042	46 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	9.2 mm ² /s
Viscosity Index	ASTM D2270	110
Flash Point	ASTM D92	>100°C
Pour Point	ASTM D97	-30°C
Total Base Number	ASTM D2896	1.2 mgKOH/g
Sulphated Ash	ASTM D874	0.25 wt %

Product nr: 4294

Date Issued: 08/08/2011

Date Superseded: 07/07/2010

Revision nr: 01