

**Product Data Sheet:** 

## **MOTORCYCLE OIL SYN 2T**

Revision nr: 01

## **Product Description:**

Product nr: 4295

MOTORCYCLE OIL SYN 2T is a fully synthetic lubricant developed for air & water cooled 2-stroke engines. MOTORCYCLE OIL SYN 2T's special formulation ensures excellent engine protection, cleanliness and low smoke even under extreme operating conditions.

MOTORCYCLE OIL SYN 2T offers very good lubricity against piston scuffing and wear of engine components. The advanced formulation provides exceptional control against engine deposits, exhaust system blocking and extended engine life without power loss, and reduces visible exhaust smoke. Low ash additive technology prevents pre-ignition and spark plug and easy miscibility with gasoline ensure stable homogeneous mixture even at low ambient temperatures.

**MOTORCYCLE OIL SYN 2T** is recommended for high-powered 2-stroke motorcycles/ scooters operating under different conditions.

**MOTORCYCLE OIL SYN 2T** is suitable for oil-injection and premix lubrication systems; always follow manufacturer's recommendations for oil-fuel ratio.

**MOTORCYCLE OIL SYN 2T** is also suitable for 2-stroke engines in all terrain vehicles, snow mobiles, lawn mowers and other applications requiring oils of this quality.

## **Specifications:**

Date Issued: 08/08/2011

**Exceeds:** API TC, ISO-L-EGD, JASO FD

Property:	<b>Test Method:</b>	Typical Values:
Density @ 15°C	<b>ASTM D4052</b>	878 kg/m <sup>3</sup>
Kinematic Viscosity @ 40°C	<b>ASTM D7042</b>	68 mm <sup>2</sup> /s
Kinematic Viscosity @ 100°C	<b>ASTM D7042</b>	11 mm <sup>2</sup> /s
Viscosity Index	<b>ASTM D2270</b>	150
Flash Point	ASTM D92	>90°C
Pour Point	ASTM D97	-45°C
Total Base Number	<b>ASTM D2896</b>	1.6 mgKOH/g
Sulphated Ash	ASTM D874	0.13 wt %

Date Superseded: 07/07/2010