



Product Data Sheet:

AUTOGEAR OIL EP 85W-140

Product Description:

AUTOGEAR OIL EP 85W-140 is a high performance gear lubricant designed to provide effective in a wide range of automotive transmissions and axle drives where API GL-4 quality oils are specified.

AUTOGEAR OIL EP 85W-140 is formulated from carefully base stocks and well balanced extreme pressure additives. **AUTOGEAR OIL EP 80W-90** gives excellent protection towards gear components against wear and scoring. Furthermore **AUTOGEAR OIL EP 85W-140** provides very good anti-corrosion protection and has been carefully inhibited against the formation of foam.

AUTOGEAR OIL EP 85W-140 is recommended for manual transmissions and transaxles requiring oils meeting API GL-4 and for on-road passenger cars, light and heavy duty trucks, buses and vans. **AUTOGEAR OIL EP 85W-140** is also recommended for off-highway equipment in construction, mining and agriculture.

AUTOGEAR OIL EP 85W-140 exceeds the specifications of API GL-4 and US MIL-L-2105, as well as the requirements of most “Original Equipment Manufacturers” (OEMs).

Specifications:

Exceeds: API GL-4, US Army MIL-L-2105

Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J306	85W-140
Density @ 15°C	ASTM D4052	907 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D7042	410 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	28.9 mm ² /s
Low-Temperature Brookfield Viscosity @ -12°C	ASTM D2983	<150000 cP
Viscosity Index	ASTM D2270	96
Flash Point	ASTM D92	210°C
Pour Point	ASTM D97	-15°C

Product nr: 4304	Date Issued: 08/08/2011	Date Superseded: 08/07/2010	Revision nr: 01
------------------	-------------------------	-----------------------------	-----------------