



Product Data Sheet:

AUTOGEAR OIL MP 85W-90

Product Description:

AUTOGEAR OIL MP 85W-90 is a high performance gear lubricant designed to provide excellent lubrication in a wide range of heavy duty automotive transmissions, axles and final drives where an API GL-5 oil is specified.

AUTOGEAR OIL MP 85W-90 is formulated from carefully selected base stocks and well balanced extreme pressure additives. **AUTO GEAR OIL MP 85W-90** gives excellent protection towards gear components regarding wear and scoring. Furthermore **AUTO GEAR OIL MP 85W-90** provides very good anti-corrosion protection and has been carefully inhibited against the formation of foam.

AUTOGEAR OIL MP 85W-90 exceeds the specifications of API GL-5 and MIL-L-2105D, as well as the requirements of most “Original Equipment Manufacturers” (OEMs).

AUTO GEAR OIL MP 85W-90 is suitable for heavy duty non-synchronized manual transmissions, axles and final drives requiring oils meeting API GL-5 in on road passenger cars, light- and heavy duty trucks, buses and vans and is also recommended for off highway equipment, in construction, mining and agriculture.

Specifications:

Exceeds: API GL-5, US Army MIL-L-2105D, MB 235.6, ZF TE-ML 05A/16C/17B/19B/21A

Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J306	85W-90
Density @ 15°C	ASTM D4052	905 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D7042	155 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	17.2 mm ² /s
Low-Temperature Brookfield Viscosity @ -12°C	ASTM D2983	<150000 cP
Viscosity Index	ASTM D2270	95
Flash Point	ASTM D92	205°C
Pour Point	ASTM D97	-21°C

Product nr: 4307	Date Issued: 08/08/2011	Date Superseded: 09/11/2010	Revision nr: 01
------------------	-------------------------	-----------------------------	-----------------