



Product Data Sheet:

ATF CVT FLUID

Product Description:

ATF CVT FLUID is an ultra high performance transmission oil formulated with selected base stocks and specially recommended for use in the latest generations of Continuously Variable Transmission (CVT) - gearboxes which transfer traction via steel-made traction chains or push-belts.

ATF CVT FLUID offers outstanding antiwear protection even under severe operating conditions and meets the most demanding requirements of a CVT transmission. **ATF CVT FLUID** offers excellent low temperature properties and ensures very stable friction coefficients over the entire service time for reliable power transmission and lowest friction losses. The special additive package ensures best ageing and oxidation stability as well as outstanding protection against foaming which is specially required in CVT transmissions.

ATF CVT FLUID has been tested successfully to be used in many CVT's of various brands such as Audi Multitronic & Mercedes Benz Autotronic. The drain intervals of the Original Equipment Manufacturers (OEMs) are mandatory.

Specifications:

Exceeds: MB 236.20, Ford WSS-M2C928-A, BMW 83 22 0 136 376/BMW 83 22 0 429 154
VW TL 521 80 (G 052 180)

| Property: | Test Method: | Typical Values: |
|-----------------------------|---------------------|------------------------|
| Density @ 15°C | ASTM D4052 | 848 kg/m ³ |
| Kinematic Viscosity @ 40°C | ASTM D7042 | 34 mm ² /s |
| Kinematic Viscosity @ 100°C | ASTM D7042 | 7 mm ² /s |
| Dynamic Viscosity @ -40°C | ASTM D5293 | 11.900 mPa.s |
| Viscosity Index | ASTM D2270 | 173 |
| Flash Point (COC) | ASTM D92 | 210°C |
| Pour Point | ASTM D97 | -51°C |
| Foaming Tendency Seq.I/II | ASTM D892 | 30/0//30/0 |
| Colour | Visual | Amber |

Product nr: 4325

Date Issued: 31/05/2012

Date Superseded: 08/08/2011

Revision nr: 01