



Product Data Sheet:

ANTIFREEZE XL

Product Description:

ANTIFREEZE XL is a good quality modern antifreeze belonging to a generation silicate-holding, nitrite-, amine- and phosphate free cooling fluid composed of mono ethylene glycol and specially selected additives.

ANTIFREEZE XL can be used throughout the year in all cooling systems in petrol- and diesel engines. Thanks to the balanced additive package and the high quality mono-ethylene glycol, this standard quality anti freeze is one of the highest quality anti freezes in the market.

ANTIFREEZE XL gives the best protection if it is used in concentrations between 40 and 50% in water.

ANTIFREEZE XL offers good protection of all metals in the cooling system and engine and is neutral towards seals and flexible hoses.

WARNING:

**Keep all anti freezes out of reach of children! Do not drink antifreeze!
If swallowed, induce vomiting and immediately call for a doctor!**

Specifications:

Exceeds: ASTM D3306, MB 325.2, BMW, Behr (Radiators) Deutz/MWM, CUNA NC956-16, GM/Opel ONORM V5123, UNE 26-361, VW TL 774C

Property:	Test Method:	Typical Values:
Colour	-	Blue/green
Density @ 15°C	ASTM D1298	1130 kg/m ³
Freezing point @ 40% in water	ASTM D1177	-28°C
Freezing point @ 50% in water	ASTM D1177	-38°C
pH (50% in water)	ASTM D1287	7.2

Product nr: 4395

Date Issued: 08/11/2011

Date Superseded: 12/07/2010

Revision nr: 01