



Product Data Sheet:

COOLANT RTU 40

Product Description:

COOLANT RTU 40 (Ready To Use) is a modern British Standard quality cooling fluid, composed of mono ethylene glycol and specially selected additives.

COOLANT RTU 40 can be used throughout the year in all cooling systems in petrol- and diesel engines. Thanks to the balanced additive package and the high quality mono-ethylene glycol, this standard quality cooling fluid is one of the highest quality cooling fluids in the market.

COOLANT RTU 40 should be used undiluted, only then the coolant gives a protection to -26°C.

COOLANT RTU 40 offers good protection of all metals in the cooling system and engine and is neutral towards seals and flexible hoses.

WARNING:

**Keep all cooling fluids out of reach of children! Do not drink cooling fluids!
If swallowed, induce vomiting and immediately call for a doctor!**

Specifications:

Exceeds: ASTM D3306, AFNOR 15-601, BS 6580, CUNA NC956-16, SAE J 1034

Property:	Test Method:	Typical Values:
Colour	-	Blue
Density @ 15°C	ASTM D1298	1060 kg/m ³
Freezing point @ 40% in water	ASTM D1177	-26°C
pH (50% in water)	ASTM D1287	7.2

Product nr: 4396

Date Issued: 08/11/2011

Date Superseded: 12/07/2010

Revision nr: 01