



**Product Data Sheet**

**COMPRESSOR OIL VDL 68**

**Product Description:**

**COMPRESSOR POWER 68** is a high performance ashless air compressor oil specially designed to meet the stringent requirements of major compressor manufacturers. **COMPRESSOR OIL VDL 68** is suited for reciprocating air-, rotary screw and vane compressors. Also used in circulating oil systems, plain and rolling element bearings, lightly loaded Gear sets, etc

**COMPRESSOR OIL VDL 68** is based on high quality mineral base oil in combination with an unique additive package to ensure the following properties.

- Excellent thermo- and oxidation stability
- Improved equipment reliability, availability and efficiency.
- Low ash and carbon forming tendency ensures improved valve performance
- Reduced potential for fires and explosions in the discharge systems.
- Exceptional wear and rust.
- Superior demulsibility reduces oil carryover and corrosion, maintains lubrication efficiency.
- Reduces sludge formation and improves life of coalesces

**COMPRESSOR OIL VDL 68** exceeds the following performance criteria:

DIN 51506 VBL/VCL/BDL

ISO 6743 DAA/DAB/DAG/DAH

Property	Unit	Test Method	Typical Value
ISO VG Class			68
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	883.7
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	71.2
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	9.1
Viscosity Index		ASTM D2270	99
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-21
FZG A/8, 3/90°C		DIN 51354-2	12
Demulsibility @54°C, max	min	DIN 51999	30

Product Nr: 4382

Date Issued: 18-07-2010

Date Superseded: -

Revision nr: -