



**Product Data Sheet**

**AUTOGEAR OIL MTF 75W-80**

**Product Description:**

AUTOGEAR OIL MTF 75W-80 is a high quality manual transmission fluid designed for passenger- and light commercial vehicles using both manual transmissions and transaxles. Not suitable for differentials and other API: GL-5 applications

AUTOGEAR OIL MTF 75W-80 is based on high quality synthetic technology base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Superior lubricating properties provide improved fuel economy.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Good gear engagement with a variety of synchronizer materials including brass, carbon, sintered bronze and molybdenum

AUTOGEAR OIL MTF 75W-80 exceeds the following performance criteria.:

API: GL-4 GM 1940182 MB 235.10 Honda MTF II VW G 052 171 VW G 060 726	BMW MTF LT-2 GM 1940764 PSA B71 2230 Volvo 97308 VW G 052 178 VW G50	BMW MTF LT-3 GM 1940768 MTF94 Volvo 97309 VW G 052 512 Renault	Ford WSD-M2C200-C Ford WSS-M2C200-D Honda MTF VW G 009 317 VW G 052 726
--	---	---	---

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	75W-80
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	869
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	55
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	9.4
Brookfield Viscosity @-40°C	cP	ASTM D2983	120000
Viscosity Index		ASTM D2270	156
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-36

Product Nr: 4338

Date Issued: 08-10-2015

Date Superseded:

Revision nr: -