



# SQUBE on track

CEILING SURFACE



## 1.0 LED

LED 6W | 220-240VAC | 50-60Hz  
COB 3-step | incl. PS | phase-cut dim  
aluminium powder coated  
incl. 1-phase track adapter

0.36kg IP20 3-0.3-D 36°

90° 355°

CODE
144164W
144164B

### Light Colour Selection

LUMEN   CRI	CODE
2200K 320   >80	1
2700K 480   >80	2
3000K 480   >80	4

more 1-phase track accessories on page 480

### OPTIONAL

dimmer

CODE
90019017
90019018

more specs on page 470

## 1.0 PAR16

PAR16 max.50W | GU10  
220-240VAC | 50-60Hz  
aluminium powder coated  
incl. 1-phase track adapter

0.32kg IP20 3-0.9-D 36°

90° 355°

CODE
144120W0
144120B0

### OPTIONAL

PAR16 LED GU10 6W  
phase-cut dim

CODE
901228W2
901228W4
901229S9

more lamps and specs on page 471

more 1-phase track accessories on page 480

## 2.0 LED

LED 12W | 220-240VAC | 50-60Hz  
COB 3-step | incl. PS | phase-cut dim  
aluminium powder coated  
incl. 3-phase track adapter

0.36kg IP20 3-0.3-D 24°

90° 355°

CODE
144364W
144364B

### Light Colour Selection

LUMEN   CRI	CODE
2700K 780   >80	2
3000K 810   >80	4

### OPTIONAL

dimmer

CODE
90019017
90019018

for switch

for din rail

more specs on page 470