





HEXO

CEILING SURFACE



2.0 LED

2xLED 8W | 220-240VAC | 50-60Hz
COB 2-step | incl. PS | phase-cut dim
aluminium powder coated
brushed

1.23kg IP20 ± 0.3 Δ 36°

| | CODE |
|--|---------|
| | 146664W |
| | 146664G |
| | 146664Q |
| | 146664P |
| | 146664B |

Light Colour Selection

| | LUMEN | CRI | CODE |
|------------|-------|-----|------|
| 2700K | 2x480 | >80 | 2 |
| 3000K | 2x480 | >80 | 4 |
| 1800-2850K | 2x410 | >90 | 9 |

2.0 PAR16

2xPAR16 max.35W | GU10
220-240VAC | 50-60Hz
aluminium powder coated
brushed

1.19kg IP20 ± 0.9

| | CODE |
|--|----------|
| | 146620W0 |
| | 146620G0 |
| | 146620Q0 |
| | 146620P0 |
| | 146620B0 |

OPTIONAL

PAR16 LED GU10 6W
phase-cut dim

| | CODE |
|------------|----------|
| 2700K | 901228W2 |
| 3000K | 901228W4 |
| 1800-2850K | 901229S9 |

more lamps and specs on page 471

OPTIONAL

inner cover max. 10 W

| | CODE |
|--|----------|
| | 911031W1 |
| | 911031G1 |
| | 911031B1 |

