



# SQUBE on base

CEILING SURFACE



## 1.0 LED

LED 6W | 220-240VAC | 50-60Hz  
COB 3-step | incl. PS | phase-cut dim  
aluminium powder coated

0.43kg IP20 0.3+D 36°

90° 355°

| CODE    |
|---------|
| 144264W |
| 144264B |

### Light Colour Selection

| LUMEN   CRI     | CODE |
|-----------------|------|
| 2200K 315   >80 | 1    |
| 2700K 480   >80 | 2    |
| 3000K 480   >80 | 4    |

## OPTIONAL

dimmer

| CODE     |
|----------|
| 90019017 |
| 90019018 |

more specs on page 470



## 1.0 PAR16

PAR16 max.50W | GU10  
220-240VAC | 50-60Hz  
aluminium powder coated

0.43kg IP20 0.9+D

90° 355°


| CODE     |
|----------|
| 144220W0 |
| 144220B0 |

## OPTIONAL

PAR16 LED GU10 6W  
phase-cut dim

| CODE     |
|----------|
| 901228W2 |
| 901228W4 |
| 901229S9 |

more lamps and specs on page 471



## 2.0 LED

LED 12W | 220-240VAC | 50-60Hz  
COB 3-step | incl. PS | phase-cut dim  
aluminium powder coated

0.38kg IP20 0.3+D 24°

90° 355°

| CODE    |
|---------|
| 144464W |
| 144464B |

### Light Colour Selection

| LUMEN   CRI     | CODE |
|-----------------|------|
| 2700K 780   >80 | 2    |
| 3000K 810   >80 | 4    |

## OPTIONAL

dimmer

| CODE     |
|----------|
| 90019017 |
| 90019018 |

more specs on page 470