

## Productsheet

# SYNTIX EVO 10W40 Semi-Synthetic

### SYNTIX EVO 10W40 Semi-Synthetic

SYNTIX EVO 10W40 Semi-Synthetic is a high quality synthetic-based engine oil developed to meet ACEA A3/B4-08 specifications and the Euro IV norms. This lubricant is perfectly applicable to most gasoline and diesel engines, both normally aspirated and supercharged. The product is highly recommended for direct injection diesel engines, such as the CDI, HDI and Common Rail engines. The product maintains a very good fluidity under challenging weather conditions, allowing it to be used during the entire year.

### Essential benefits

- Provides a full engine protection and improves its oil drain interval
- Maintains an excellent fluidity at low temperatures

### SPECIFICATIONS

API SL /CF  
MB 229.1  
VW 501 01

VW 505 00  
ACEA A3/B3-10  
ACEA A3/B4-08

### TYPICAL VALUES

SYNTIX EVO 10W40 Semi-Synthetic	unit	value	method
Density at 15°C	kg/m <sup>3</sup>	866	ASTM D4052
Viscosity at 40°C	mm <sup>2</sup> /s	91	ASTM D445
Viscosity at 100°C	mm <sup>2</sup> /s	13.8	ASTM D445
Viscosity index		155	ASTM D2270
B.N. (HClO <sub>4</sub> method)	mg KOH/g	8.3	ASTM D2896
Pour point	°C	-39	ASTM D6892
CCS viscosity at -25°C	mPa.s	6700	ASTM D5293
Sulfated Ash	Mass %	1.0	ASTM D874
Flash Point COC	°C	220	ASTM D92

Specification variations in these characteristics may occur.  
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.