

Productsheet

SYNTIX EVO LLIII – PSFD 5W30

SYNTIX EVO – PSFD Full Synthetic Motor Oil

With Performance Strength and Flow Dynamics (PSFD), SYNTIX EVO is a full synthetic high quality oil of the latest generation. The product meets the highest standards for gasoline and diesel engines. The combination of a high quality synthetic base oil and optimized additives results into an exceptional viscosity index for additional protection, very high thermal stability and excellent fluidity at low temperatures and when starting. These characteristics ensure maximum protection against engine wear, at low and high temperatures. The oil also contributes to improved fuel economy.

Essential benefits

- Aftertreatment protection: full aftertreatment system protection.
- Total engine protection: outstanding engine cleanliness and durability.
- Fuel economy: superior fuel economy and CO₂ reduction.

SPECIFICATIONS

ACEA C3-10	Porsche C30	BMW Longlife-04
ACEA C2*	VW 504 00	
MB 229.51	VW 507 00	

TYPICAL VALUES

SYNTIX EVO LLIII – PSFD 5W30	Method	unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.853
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	70
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.6
Viscosity Index	ASTM D2270	-	161
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	6.3
Pourpoint	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa.s	5600
Sulfated Ash	ASTM D874	Mass %	0.7
Flashpoint	ASTM D92	°C	230

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.