

## Productsheet

# SYNTIX EVO 5W30 DEXOS II

---

### SYNTIX EVO 5W30 DEXOS II

SYNTIX EVO 5W30 DEXOS II is a full synthetic high-performance engine oil developed using an advanced technology for Mid SAPS catalyst compatible engine oils. This created an engine oil enhancing the fuel economy and extending service life. It also reduces ash formation protecting particulate filters and exhaust after-treatment devices. The Dexos II specification is required for all new GM/Opel/Vauxhall/Chevrolet diesel and gasoline models and is backward compatible to older specifications (GM-LL-A-025 and GM-B-LL-025).

### Essential benefits

- Provides a full after-treatment systems protection
- Creates a superior fuel economy and CO2 reduction
- Provides a full engine protection and improves its durability

### SPECIFICATIONS

API SN /CF	VW 505 01
MB 229.51	ACEA C3-10
VW 502 00	BMW LONGLIF E-04
VW 505 00	GM dexos 2
VW 505 01	ACEA C2*

### TYPICAL VALUES

SYNTIX EVO 5W30 DEXOS II	unit	value	method
Density at 15°C	kg/m <sup>3</sup>	855	ASTM D4052
Viscosity at 40°C	mm <sup>2</sup> /s	67.1	ASTM D445
Viscosity at 100°C	mm <sup>2</sup> /s	12.2	ASTM D445
Viscosity index		182	ASTM D2270
B.N. (HClO <sub>4</sub> method)	mg KOH/g	7.2	ASTM D2896
Pourpont	°C	-36	ASTM D6892
CCS viscosity at -30°C	mPa.s	6280	ASTM D5293
Sulfated Ash	Mass %	0.77	ASTM D874
Flash Point COC	°C	234	ASTM D92

Specification variations in these characteristics may occur.  
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.