

Productsheet

SYNTIX EVO 5W40

SYNTIX EVO 5W40

SYNTIX EVO 5W40 is a high quality engine oil, specially designed to meet the strict requirements of manufacturers. Thanks to its advanced selected composition, it provides a strong oil film guaranteeing a high lubricating power, a very low resistance when starting, an exceptional viscosity index and a very high thermal stability.

Essential benefits

- Provides a total engine protection
- Keeps the engine internals clean

SPECIFICATIONS

API SN /CF	PSA B71 2296
VW 502 00	MB 229.3
VW 505 00	MB 226.5
ACEA A3/B4-08	RENAULT RN 0710
RENAULT RN 0700	OPEL GM-LL -B-025
BMW LONGLIFE -01	PORSCHE A40

TYPICAL VALUES

SYNTIX EVO 5W40	unit	value	method
Density at 15°C	kg/m ³	856	ASTM D4052
Viscosity at 40°C	mm ² /s	86	ASTM D445
Viscosity at 100°C	mm ² /s	14.4	ASTM D445
Viscosity index		175	ASTM D2270
B.N. (HCLO4 method)	mg KOH/g	9.6	ASTM D2896
Pourpont	°C	-33	ASTM D6892
CCS viscosity at -15°C	mPa.s	6100	ASTM D5293
Sulfated Ash	Mass %	1.2	ASTM D874
Flash Point COC	°C	220	ASTM D92

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.