

Productsheet

SYNTIX MAX TECH1 10W60

SYNTIX MAX TECH1 10W60

SYNTIX MAX TECH1 10W60 is a full synthetic high performance engine oil. The product meets the highest standards for competition and road use in gasoline and diesel engines. The combination of a high quality PAO synthetic base oil and optimized additives results into an expanded viscosity range for additional protection, even at continuous maximum engine load and high RPM. Fast oil distribution ensures maximum protection against engine wear, even at low temperatures. The oil also contributes to improved fuel economy.

Essential benefits

- Creates a superior fuel economy and CO2 reduction
- Provides a full engine protection

SPECIFICATIONS

API SN /CF
MB 229.3 Level

ACEA A3/B4-08
BMW LONGLIFE-01 Level

TYPICAL VALUES

| SYNTIX MAX TECH1 10W60 | unit | value | method |
|------------------------|--------------------|-------|------------|
| Density at 15°C | kg/m ³ | 855 | ASTM D4052 |
| Viscosity at 40°C | mm ² /s | 156 | ASTM D445 |
| Viscosity at 100°C | mm ² /s | 25 | ASTM D445 |
| Viscosity index | | 194 | ASTM D2270 |
| B.N. (HClO4 method) | mg KOH/g | 9.5 | ASTM D2896 |
| Pour point | °C | -36 | ASTM D6892 |
| CCS viscosity at -25°C | mPa.s | 3800 | ASTM D5293 |
| Sulfated Ash | Mass % | 1.0 | ASTM D874 |
| Flash Point COC | °C | 235 | ASTM D92 |

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.