

Productsheet

SYNTIX GEARMAX – DGP 75W90

SYNTIX GEARMAX – DGP Full Synthetic Gear Oil – 75W90

With Dynamic Gear Protection (DGP), this is a full synthetic high performance low friction gear oil. The oil is a combination of a high quality synthetic base oil and innovative additives, resulting into a high performance level in all conditions. This makes SYNTIX GEARMAX perfectly suited for all types of gears in competition and road use cars, motorcycles and construction machines. Its characteristics ensure smooth operation and thus contribute to a longer life span of the running components.

The essential benefits :

- Good gear operation at low temperatures
- Excellent cold flow properties
- Distinctive wear protection under all operation conditions
- Good synchron suitability
- High aging stability

SPECIFICATIONS

API GL-4 & GL-5 & MT-1
MB 235.6
MIL-PRF-2105 D&E

MAN 3343
ZF TE-ML 02B, 05A, 07A, 08, 16B, 17A&B

TYPICAL VALUES

SYNTIX GEARMAX – DGP 75W90	unit	value	method
Density at 15°C	kg/m ³	861	DIN 51 757
Viscosity at 40°C	mm ² /s	74,30	DIN 51 562
Viscosity at 100°C	mm ² /s	14,23	DIN 51 562
Viscosity Index		200	DIN ISO 2909
Pourpoint	°C	-51	DIN ISO 3016
Flashpoint	°C	190	DIN ISO 2592

ARTICLE-NO. 1I: 8718692740198

ARTICLE-NO. 5I: 8718692740204

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.