

Productsheet

SYNTIX EVO 5W30 C2 PSA SN/CF

SYNTIX EVO 5W30 C2 PSA SN/CF

SYNTIX EVO 5W30 C2 PSASN/CF is a full synthetic high-performance engine oil specifically developed to ensure the highest fuel economy and lowest CO₂ emissions. This low viscosity oil is recommended for Citroën and Peugeot gasoline and diesel engines equipped with diesel particulate filters. It also meets current requirements of most Japanese OEM's, including Toyota, Honda, Subaru and Nissan.

Essential benefits

- Provides a full after-treatment systems protection
- Creates a superior fuel economy and CO₂ reduction
- Provides a full engine protection and improves its durability

SPECIFICATIONS

API SN /CF
ACEA C2-10
RENAULT RN 0700

PSA Oil meeting specification B71 2290
FIAT 9.55535-S1

TYPICAL VALUES

SYNTIX EVO 5W30 C2 PSA SN/CF	unit	value	method
Density at 15°C	kg/m ³	856	ASTM D4052
Viscosity at 40°C	mm ² /s	57	ASTM D445
Viscosity at 100°C	mm ² /s	10.1	ASTM D445
Viscosity index		167	ASTM D2270
B.N. (HCLO ₄ method)	mg KOH/g	7.5	ASTM D2896
Pourpont	°C	-39	ASTM D6892
CCS viscosity at -15°C	mPa.s	5500	ASTM D5293
Sulfated Ash	Mass %	0.79	ASTM D874
Flash Point COC	°C	232	ASTM D92

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.