

## Productsheet

# SYNTIX ATF DEXRON II

---

### SYNTIX ATF DEXRON II

This oil has been developed for automatic transmissions, power steering systems, torque convertors and hydraulic circuits where fabricators request lubricants with the Dexron II specification. The product has an optimal chemical stability, high viscosity index and offers an excellent protection against wear of the essential parts.

#### Essential benefits

- Extended transmission life.
- Optimized thermal and oxidation stability.

#### SPECIFICATIONS

FORD MERCON	MB 236.5
MB 236.7	ZF TE-ML 03D
ALLISON C4	ZF TE-ML 04D
MAN 339 V1/Z1	ZF TE-ML 09
GM 6137-M DEXRON II -D	ZF TE-ML 11A
VOITH H55.6335xx	ZF TE-ML 14A
CATERPILLAR TO -2	ZF TE-ML 17C

#### TYPICAL VALUES

SYNTIX ATF DEXRON II	unit	value	method
Color		red	ASTM D1500
Density at 15°C	kg/m <sup>3</sup>	856	ASTM D4052
Viscosity at 40°C	mm <sup>2</sup> /s	37	ASTM D445
Viscosity at 100°C	mm <sup>2</sup> /s	7.4	ASTM D445
Viscosity index		170	ASTM D2270
Pourpoint	°C	-39	ASTM D6892
Brookfield viscosity at -40°C	mPa.s	45000	ASTM D2983

Specification variations in these characteristics may occur.  
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.