

Productsheet

SYNTIX ATF DEXRON III

SYNTIX ATF DEXRON III

SYNTIX ATF DEXRON III is a semi-synthetic oil with a high viscosity index developed for most automatic transmissions. This high quality fluid ensures an optimal performance, even at low operating temperatures. It also provides smooth switching and driving comfort. This product is applicable to uses where manufacturers prescribe products meeting the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon requirements.

Essential benefits

- Enables excellent gear shifting performance
- Extends the transmission life substantially
- Provides excellent thermal and oxidation stability

SPECIFICATIONS

FORD MERCON	VOLVO ST D 1273,41 (97341)
MB 236.5	ZF TE-ML 03D
MB 236.9	ZF TE-ML 04D
MAN 339 V1/Z1	ZF TE-ML 09
GM 6417-M DEXRON III -G	ZF TE-ML 11B
VOITH H55.6335xx	ZF TE-ML 14A
ALLISON C4	ZF TE-ML 17C
VOLVO ST D 1273,40 (97340)	

TYPICAL VALUES

SYNTIX ATF DEXRON III	unit	value	method
Color		rood	ASTM D1500
Density at 15°C	kg/m ³	885	ASTM D4052
Viscosity at 40°C	mm ² /s	33.9	ASTM D445
Viscosity at 100°C	mm ² /s	7.1	ASTM D445
Viscosity index		179	ASTM D2270
Pourpont	°C	-45	ASTM D6892
Brookfield viscosity at -40°C	mPa.s	17500	ASTM D2983
Flash Point COC	°C	196	ASTM D92

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.