

Productsheet

SYNTIX PRO IND LD TURBO 10W40

SYNTIX PRO IND LD TURBO 10W40

SYNTIX PRO IND LD TURBO 10W40 is a full synthetic long-drain engine oil is developed for an optimal lubricants of modern heavy duty diesel engines. This high performance oil maintains a perfect viscosity, even at very low or hot temperatures. It also cleans the vital engine parts thoroughly and recedes hazardous exhaust emissions.

This oil increases the oil intervals extensively.

Essential benefits

- Provides a full after-treatment systems protection
- Creates a superior fuel economy and CO₂ reduction
- Provides a full engine protection and improves its durability

SPECIFICATIONS

MB 228.5
MAN M3277
ACEA E7-08 Issue 2
SCANIA LDF-3
VOLVO VDS-3
MACK EO-N
API CF
ACEA E4-08 Issue 2
CUMMINS CES 20072

MTU Type 3
RENAULT RD-2
RENAULT RLD
RENAULT RL D-2
RENAULT RXD
SCANIA LDF-2
DAF EXTENDED DRAIN
DEUTZ DQC-III-10

TYPICAL VALUES

SYNTIX PRO IND LD TURBO 10W40	unit	value	method
Density at 15°C	kg/m ³	870	ASTM D4052
Viscosity at 40°C	mm ² /s	86.3	ASTM D445
Viscosity at 100°C	mm ² /s	13.3	ASTM D445
Viscosity index		155	ASTM D2270
B.N. (HClO ₄ method)	mg KOH/g	16.1	ASTM D2896
Pourpont	°C	-39	ASTM D6892
CCS viscosity at -25°C	mPa.s	6700	ASTM D5293

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.