

## Productsheet

# SYNTIX PRO IND LD 5W30

### SYNTIX PRO IND LD 5W30

This advanced, full-synthetic long-drain diesel engine oil meets the most demanding specification requirements for heavy trucks. The product has been developed to provide the best lubrication while meeting the latest and severest requirements of European exhaust emission regulations. The oil provides an optimal cleaning, lengthens the oil interval and maintains a perfect lubrication even during hot and cold temperatures.

\*This engine oil is not suited for petrol engines or diesel engines fitted with after diesel partical filters.

### Essential benefits

- Total engine protection: outstanding engine cleanliness and durability.
- Cold start: excellent fluidity at low temperature.
- Drain interval extension : very long oil drain interval.

### SPECIFICATIONS

ACEA E4-08 Issue 2	MB 228.5
ACEA E7-08 Issue 2	MTU Type 3
API CI-4	RENAULT RL D-2
DAF EXTENDED DRAIN	RENAULT RD-2
DEUTZ DQC-IV-10	RENAULT RLD
MACK EO-N	RENAULT RXD
MACK EO-N Premium Plus	SCANIA Field Trial Running
MAN M3277	VOLVO VDS-3

### TYPICAL VALUES

SYNTIX PRO IND LD 5W30	unit	value	method
Density at 15°C	kg/m <sup>3</sup>	861	ASTM D4052
Viscosity at 40°C	mm <sup>2</sup> /s	73.2	ASTM D445
Viscosity at 100°C	mm <sup>2</sup> /s	12.2	ASTM D445
Viscosity index		165	ASTM D2270
B.N. (HClO <sub>4</sub> method)	mg KOH/g	15.4	ASTM D2896
Pourpont	°C	-45	ASTM D6892
CCS viscosity at -30°C	mPa.s	6050	ASTM D5293
Sulfated Ash	Mass %	1.8	ASTM D874
Flash Point COC	°C	225	ASTM D92

Specification variations in these characteristics may occur.

The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.