

- INT 401
- INT 402
- INT 403
- INT 404
- INT 405

Description : this film provides a frosted aspect to any glass while keeping a total privacy and luminosity.

For : facades, office partitions, computer rooms, hospitals, floor level rooms, schools, workshops, decoration of devantures, etc...

Plotter cuttable, easy weeding.

Application method : internal surface with soapy water.

Glass maintenance : the film may be cleaned with soapy water, 30 days after the application. Any abrasive products that could scratch the film, are not recommended.

Durability : 10 years for inside vertical application in Central Europe.

Storage : 2 years from the delivery date. This film has to be kept away from excessive humidity. It also has to be stored away from direct sunlight at a temperature under 38°C.

Important factors : the glass surface used must be entirely dirt free and any grease or other filth must be removed prior to installation. Gas may be given off from certain polycarbonate surfaces which are too new or of mediocre quality. This may be unsightly but does not lessen the adhesive qualities of the film. Users are recommended to carry out a trial beforehand to avoid bubbling issues.

Material	PVC 80 microns
Adhesive	Acrylic polymer 20 gr/m ²
Colour INT 401	Grey frosted
Colour INT 402	Sparkle frosted
Colour INT 403	Pink sparkle frosted
Colour INT 404	Green sparkle frosted
Colour INT 405	Blue sparkle frosted
Release liner	Siliconed paper 100 microns
Application	Internal
Dimensions	47,25" x 8,20'
	47,25" x 33,34'
	47,25" x 164,04'

Fire performance class

M1

Please make sure to match the correct specifications when applying your film. You may follow the glass compatibility guideline, especially concerning thermal stress.

Please note that Réfectiv does not guaranty the glass quality or the incorrect use of its films and claims the possibility of changing the production process or tints without previous notification.