

Description : this graffiti-proof film is specially designed to facilitate the cleaning of graffiti* and to protect glass against attacks and intentional scratches. The thickness of the film acts as a barrier between the glass and the aggressor. The glass surface remains intact. The film can easily be replaced to give the glass its original look.

For : devantures, floor level glazing, entrance halls, street furniture, public transportation, etc...

Application method : internal & external surfaces with soapy water.

Glass maintenance : the film may be cleaned with soapy water, 30 days after the application. Any abrasive products that could scratch the film, are not recommended. Do not apply any stickers, or any other type of adhesives on the film.

Durability : 5 to 8 years for vertical application in Central Europe.

Storage : 2 years from the delivery date. This film has to be kept away from excessive humidity. It also has to be stored away from direct sunlight at a temperature under 38°C.

Important factors : the glass surface used must be entirely dirt free and any grease or other filth must be removed prior to installation. Gas may be given off from certain polycarbonate surfaces which are too new or of mediocre quality. This may be unsightly but does not lessen the adhesive qualities of the film. Users are recommended to carry out a trial beforehand to avoid bubbling issues.

**The anti-graffiti film resists to most solvents and can be cleaned, but it can also be easily removed and replaced in just few minutes in case of permanent TAG. It protects against scratches as well.*

Material	Polyester 100 microns
Adhesive	Acrylic polymer 17 gr/m ²
Tint	Incolored
Release liner	Siliconed polyester 23 microns
Application	Internal & External
U.V. transmission	5 %
U.V. resistance	Excellent
Scratch resistance	Excellent
Graffiti resistance	Excellent
Thermal resistance	from -20°C to 80°C
Application temperature	Minimum 5°C
Dimensions	60'' x 8,34' 60'' x 33,34' 60'' x 100'

Fire performance class

M1

Please make sure to match the correct specifications when applying your film. You may follow the glass compatibility guideline, especially concerning thermal stress.

Please note that Reflectiv does not guaranty the glass quality or the incorrect use of its films and claims the possibility of changing the production process or tints without previous notification.

