

## **Technical data**

## Fuschia 60026

**Description:** applied on a clear glazing, this adhesive film gives a fuchsia colour without altering the transparency of the glass.

For: decoration, partitions, shower screens, glass furniture, inside facades, glass made partitions.

Application method: internal surface with soapy water.

Glass maintenance: the film may be cleaned with soapy water, 30 days after the application. Any abrasive products that could scratch the film, are not recommended. Do not apply any stickers, or any other type of adhesives on the film.

**Durability:** 10 to 12 years on any glazing away from direct sunlight.

**Storage**: 2 years from the delivery date. This film has to be kept away from excessive humidity. It also has to be stored away from direct sunlight at a temperature under 38°C.

Important factors: the glass surface used must be entirely dirt free and any grease or other filth must be removed prior to installation. Gas may be given off from certain polycarbonate surfaces which are too new or of mediocre quality. This may be unsightly but does not lessen the adhesive qualities of the film. Users are recommended to carry out a trial beforehand to avoid bubbling issues.

For all glass exposed to sunlight, double pane, tinted, laminated, reinforced, please consult your Reflectiv Sales Representative for film compatibility.

Material	Polyester 23 microns	
Adhesive	Acrylic polymer 13 gr/m <sup>2</sup>	
Tint	Fuschia deep dyed	
Release liner	Siliconed polyester 23 microns	
Application	Internal	
Total solar absorption	28 %	
Visible light transmission	36 %	
U.V. transmission	2 %	
Thermal resistance	from -20°C to 80°C	
Application temperature	Minimum 5°C	
Dimensions	60" x 8,34" 60" x 33,34" 60" x 100"	



Please make sure to match the correct specifications when applying your film. You may follow the glass compatibility guideline, especially concerning thermal stress.

Please note that Réflectiv does not guaranty the glass quality or the incorrect use of its films and claims the possibility of changing the production process or tints without previous notification.



**Total Transparency**