



P - Soft Insulation

Free standing not enamelled buffer tanks

CHARACTERISTICS

Model	—	BC200(P)	BC300(P)	BC400(P)	BC500(P)	BC750	BC1000
Rated volume	L.	200	300	400	500	750	1000
Rated pressure	Mpa	0,3					
Weight when empty	kg	57	72	126	138	170	207
Weight when empty (P)	kg	30	46	86	95		

CONNECTIONS

	"GAS/F	1	1	1 ½	1 ½	2	2
1: Purge	"GAS/F	1	1	1 ½	1 ½	2	2
2: Impulsion / Return	"GAS/F	1	1 ½	1 ½	1 ½	2	2
3: Impulsion / Return - Empty	"GAS/F	1	1 ½	1 ½	1 ½	2	2
4: Temperature	"GAS/F	½	½	½	½	½	½

DIMENSIONS

Level	mm	229	228	267	267	366	366
Level A	mm	229	228	267	267	366	366
Level B	mm	373	468	454	522	538	650
Level C	mm	590	781	723	859	801	1025
Level D	mm	Ø 500		Ø 640		Ø 850	
Level E	mm	807	1093	992	1196	1063	1400
Level F	mm	Ø 586		Ø 740		Ø 1050	
Level F (P)	mm	Ø 670		Ø 810			
Level G	mm	951	1333	1180	1451	1281	1731
Level L (P)	mm	1210	1590	1480	1750	1670	2100
Level L	mm	1182	1563	1451	1721		