



WATER HEATERS "EXTRA LIFE" FOR VERTICAL MOUNTING ON THE WALL

CHARACTERISTICS

| Model | ... | 72269KA | 72267KA | 72268KA | 72265KA | 72270KA | 72266KA |
|---|-----|-----------------|-----------------|---------------|---------------|---------------|---------------|
| Rated volume | L | 30 | 50 | 80 | 80 | 100 | 120 |
| Rated pressure | MPa | 0,8 | 0,8 | 0,8 | 0,8 | 0,8 | 0,8 |
| Rated voltage | V~ | 230 | 230 | 230 | 230 | 230 | 230 |
| Rated electrical power | kW | 1,5; 2,0; 3,0 | 1,5; 2,0; 3,0 | 1,5; 2,0; 3,0 | 1,5; 2,0; 3,0 | 1,5; 2,0; 3,0 | 1,5; 2,0; 3,0 |
| Warm-up time from 12-75 °C | h | 1,5; 1,12; 0,75 | 2,5; 1,87; 1,25 | 4 ; 3; 2 | 4 ; 3; 2 | 5 ; 3,7; 2,5 | 6 ; 4,5; 3 |
| MIX 37 °C (temperature of the water in the water tank: 75 °C; water temperature of supply water: 12 °C) | L | 76 | 126 | 195 | 195 | 250 | 297 |
| Weight when empty | kg | 15 | 20 | 27 | 26.5 | 32 | 36 |

CONNECTIONS

| | | | | | | | |
|--------------------------------|--------|--------|--------|--------|--------|--------|--------|
| 1: Hot water outlet | G1/2 M | G1/2 M | G1/2 M | G1/2 M | G1/2 M | G1/2 M | G1/2 M |
| 2: Cold water inlet - Drain | G1/2 M | G1/2 M | G1/2 M | G1/2 M | G1/2 M | G1/2 M | G1/2 M |
| 3: Temperature indicator | - | - | - | - | - | - | - |
| 4: Control panel | - | - | - | - | - | - | - |
| 5: Flange with heating element | - | - | - | - | - | - | - |

DIMENSIONS

| | | | | | | | |
|---|----|-----|-----|------|-----|------|------|
| A | mm | 580 | 780 | 1095 | 860 | 1035 | 1195 |
| C | mm | 190 | 190 | 190 | 180 | 180 | 180 |
| D | mm | 400 | 400 | 400 | 475 | 475 | 475 |
| E | mm | 80 | 80 | 80 | 95 | 95 | 95 |
| F | mm | 405 | 405 | 405 | 480 | 480 | 480 |
| G | mm | 40 | 40 | 40 | 40 | 40 | 40 |