

## Productsheet

# SYNTIX PRO IND GEAR 85W140 ECO

---

### SYNTIX PRO IND GEAR 85W140 ECO

This lubricant is developed to maintain perfect performance even under the highest pressures in gearboxes. The product is recommended for hypoïdtransaxles, but can also be used for cone wheels with spiralgears, wormwheels and most transaxles. It ensures smooth gear changing, even under high RPM, shockpressure and high torques. It lengthens the lifespan of the vital parts in the transmission.

- Anti-wear protection : long transmission life
- Frictional properties : easy gear shifting.

### SPECIFICATIONS

API GL-5	MIL MIL -L-2105 C
ZF TE-ML 05A	MIL MIL -L-2105 D
ZF TE -ML 12E	ZF TE-ML 07A
ZF TE-ML 16D	ZF TE -ML 16B
ZF TE-ML 17B	ZF TE-ML 16C
ZF TE-ML 19B	

### TYPICAL VALUES

SYNTIX PRO IND GEAR 85W140 ECO	unit	value	method
Density at 15 °C	kg/m <sup>3</sup>	908	ASTM D4052
Viscosity at 40 °C	mm <sup>2</sup> /s	367	ASTM D445
Viscosity at 100 °C	mm <sup>2</sup> /s	26.1	ASTM D445
Viscosity index		95	ASTM D2270
Pourpoint	°C	-15	ASTM D6892
Copper corrosion		1B	ASTM D130
Flash Point COC	°C	215	ASTM D92

Specification variations in these characteristics may occur.

The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.