

## Productsheet

# SYNTIX EVO 5W30 C4

---

### SYNTIX EVO 5W30 C4

SYNTIX EVO 5W30 C4 is a full synthetic high-performance engine oil specifically developed to ensure a superior protection of the after-treatment systems of Renault engines. This product can be applied to both gasoline and diesel engines of passenger cars, with or without turbo, equipped with a DPF and a Three-Way-Catalyst.

### Essential benefits

- Provides a full after-treatment systems protection
- Creates a superior fuel economy and CO2 reduction
- Provides a full engine protection and improves its durability

### SPECIFICATIONS

ACEA C4-10  
MB 229.51

RENAULT RN 0720

### TYPICAL VALUES

| SYNTIX EVO 5W30 C4     | unit               | value | method     |
|------------------------|--------------------|-------|------------|
| Density at 15°C        | kg/m <sup>3</sup>  | 854   | ASTM D4052 |
| Viscosity at 40°C      | mm <sup>2</sup> /s | 68    | ASTM D445  |
| Viscosity at 100°C     | mm <sup>2</sup> /s | 11.7  | ASTM D445  |
| Viscosity index        |                    | 169   | ASTM D2270 |
| B.N. (HClO4 method)    | mg KOH/g           | 7.2   | ASTM D2896 |
| Pourpont               | °C                 | -39   | ASTM D6892 |
| CCS viscosity at -30°C | mPa.s              | 6300  | ASTM D5293 |
| Sulfated Ash           | Mass %             | 0.5   | ASTM D874  |
| Flash Point COC        | °C                 | 200   | ASTM D92   |

Specification variations in these characteristics may occur.  
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.