

Productsheet

SYNTIX EVO 20W50 SF/CC

SYNTIX EVO 20W50 SF/CC

The SYNTIX EVO 20W50 engine oil with SF/CC specification has been developed for oldtimer and youngtimer engines, used under regular conditions. This product is suitable for both petrol and naturally aspirated diesel engines with high performance and small carters. The advanced oil maintains a perfect lubrication of the vital engine parts, cleans the interior of the engine and lengthens the oil drain interval.

Essential benefits

- Provides a total engine protection
- Creates a superior fuel economy and CO2 reduction
- Maintains an excellent fluidity at low temperatures

SPECIFICATIONS

API SF/CC
MIL -L-2104 B

MIL -L-46152 B
MB 226.1

TYPICAL VALUES

SYNTIX EVO 20W50 SF/CC	unit	value	method
Density at 15°C	kg/m ³	888	ASTM D4052
Viscosity at 40°C	mm ² /s	158	ASTM D445
Viscosity at 100°C	mm ² /s	17.5	ASTM D445
Viscosity index		121	ASTM D2270
B.N. (HClO4 method)	mg KOH/g	4.4	ASTM D2896
Pourpont	°C	-27	ASTM D6892
CCS viscosity at -30°C	mPa.s	8320	ASTM D5293
Sulfated Ash	Mass %	0.50	ASTM D874
Flashpoint	°C	240	ASTM D92

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.