

## Productsheet

# SYNTIX EVO 15W40 SL/CF A3/B4

---

### SYNTIX EVO 15W40 SL/CF A3/B4

SYNTIX EVO 15W40 is an advanced mineral oil developed for high performance applications. This product meets and even exceeds ACEA A3/B4-08 specifications and is suitable for most 4-stroke gasoline passenger car engines, 4-stroke diesel engines with or without turbo and light duty trucks. This high quality oil is also compatible with biodiesel, proven in various field tests.

#### Essential benefits

- Provides a full engine protection and improves its oil drain interval

#### SPECIFICATIONS

API SL /CF  
MB 229.1

ACEA A3/B3-10  
ACEA A3/B4-08

#### TYPICAL VALUES

SYNTIX EVO 15W40 SL/CF A3/B4	unit	value	method
Density at 15°C	kg/m <sup>3</sup>	885	ASTM D4052
Viscosity at 40°C	mm <sup>2</sup> /s	103	ASTM D445
Viscosity at 100°C	mm <sup>2</sup> /s	13.7	ASTM D445
Viscosity index		130	ASTM D2270
B.N. (HClO <sub>4</sub> method)	mg KOH/g	8.3	ASTM D2896
Pour point	°C	-30	ASTM D6892
CCS viscosity at -20°C	mPa.s	6800	ASTM D5293
Sulfated Ash	Mass %	1.03	ASTM D874
Flash Point COC	°C	230	ASTM D92

Specification variations in these characteristics may occur.

The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.