

Productsheet SYNTIX EVO 5W30 C1

SYNTIX EVO 5W30 C1

SYNTIX EVO 5W30 C1 is a full synthetic high-performance engine oil developed for the latest generation EURO IV gasoline engines and diesel engines fitted with diesel particulate filters, requiring a low HTHS viscosity oil. It creates a superior fuel economy and CO2 reduction.

Essential benefits

- Provides a full after-treatment systems protection
- Creates a superior fuel economy and CO2 reduction
- Provides a full engine protection and improves its durability

SPECIFICATIONS

FORD WSS-M2C934-B ACEA C1-10 JASO DL-1

TYPICAL VALUES

SYNTIX EVO 5W30 C1	unit	value	method
Density at 15°C	kg/m³	848	ASTM D4052
Viscosity at 40°C	mm²/s	55.6	ASTM D445
Viscosity at 100°C	mm²/s	10	ASTM D445
Viscosity index		169	ASTM D2270
B.N. (HCLO4 method)	mg KOH/g	7.8	ASTM D2896
Pour point	°C	-36	ASTM D6892
CCS viscosity at -30°C	mPa.s	4000	ASTM D5293
Sulfated Ash	Mass %	0.5	ASTM D874
Flash Point COC	°C	226	ASTM D92

Specification variations in these characteristics may occur.

The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.