

Productsheet

SYNTIX EVO 5W20

SYNTIX EVO 5W20

SYNTIX EVO 5W20 is a highly advanced synthetic motor oil that meets the requirements of the new Ford EcoBoost petrol engines, specified Ford WSS-M2C948-B. It can also be used where the vehicle manufacturer specifies the required engine oil ACEA A1/B1 or API SN. The engine oil is extremely fuel efficient and ensures a reduction of both fuel consumption and exhaust emission. The excellent fluidity at low temperatures ensure a very good cold starting behavior.

Essential benefits

- Provides a total engine protection
- Creates a superior fuel economy and CO2 reduction
- Maintains an excellent fluidity at low temperatures

SPECIFICATIONS

API SN
FORD WSS -M2C948-B

ACEA A1/B1-10

TYPICAL VALUES

SYNTIX EVO 5W20	unit	value	method
Density at 15°C	kg/m ³	851	ASTM D4052
Viscosity at 40°C	mm ² /s	42.3	ASTM D445
Viscosity at 100°C	mm ² /s	7.9	ASTM D445
Viscosity index		162	ASTM D2270
B.N. (HClO4 method)	mg KOH/g	7.6	ASTM D2896
Pourpont	°C	-39	ASTM D6892
CCS viscosity at -30°C	mPa.s	5500	ASTM D5293
Sulfated Ash	Mass %	0.8	ASTM D874
Flashpoint	°C	220	ASTM D92

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.