

Productsheet

SYNTIX TWO-STROKE OIL

SYNTIX TWO-STROKE OIL

This semi synthetic two-stroke oil is developed for high performance, 2-stroke gasoline engines, scooters, ATV'S, lawn equipment and chainsaws. The product maintains its high lubrication viscosity, even under most demanding circumstances thank to its excellent thermal stability. The product can easily be mixed with gasoline and provides a strong protection against deposits.

Essential benefits

- Excellent engine performance
- Adequate corrosion protection

SPECIFICATIONS

API TC
JASO FB

ISO L-EGB

TYPICAL VALUES

SYNTIX TWO-STROKE OIL	unit	value	method
Density at 15°C	kg/m ³	882	ASTM D4052
Viscosity at 40°C	mm ² /s	78.4	ASTM D445
Viscosity at 100°C	mm ² /s	10.2	ASTM D445
Viscosity index		112	ASTM D2270
B.N. (HCLO4 method)	mg KOH/g	1.1	ASTM D2896
Pour point	°C	-15	ASTM D6892
Sulfated Ash	Mass %	0.28	ASTM D874
Flash Point COC	°C	100	ASTM D92

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.