

Productsheet

SYNTIX GEARMAX – DGP 75W90

SYNTIX GEARMAX – DGP Full Synthetic Gear Oil – 75W90

With Dynamic Gear Protection (DGP), this is a full synthetic high performance low friction gear oil. The oil is a combination of a high quality synthetic base oil and innovative additives, resulting into a high performance level in all conditions. This makes SYNTIX GEARMAX perfectly suited for all types of gears in competition and road use cars, motorcycles and construction machines. Its characteristics ensure smooth operation and thus contribute to a longer life span of the running components.

The essential benefits :

- Good gear operation at low temperatures
- Excellent cold flow properties
- Distinctive wear protection under all operation conditions
- Good synchron suitability
- High aging stability

SPECIFICATIONS

API MT-1	ZF TE-ML 02B
API GL-5	ZF TE-ML 05B
MB 235.8	ZF TE-ML 07A
SCANIA STO 1:0	ZF TE-ML 12B
MAN 341 Z-2	ZF TE-ML 16F
MAN 342 M-3	ZF TE-ML 17B
API GL 4	ZF TE-ML 19C
MIL PRF -2105E	ZF TE-ML 21B
MAN 341 E-3	DAF GL5/MIL -PRF -2105E
MACK GO-J	ARVIN MERITOR 0-76-N
RENAULT B0032/3 Annex 3	IVECO MIL -PRF -2105E

TYPICAL VALUES

SYNTIX GEARMAX – DGP 75W90	unit	value	method
Density at 15°C	kg/m ³	868	ASTM D4052
Viscosity at 40°C	mm ² /s	76.3	ASTM D445
Viscosity at 100°C	mm ² /s	15.2	ASTM D445
Viscosity Index		203	ASTM D2270
Pourpoint	°C	-48	ASTM D6892
Brookfield viscosity at -40 °C	mPa.s	45.000	ASTM D2983

Specification variations in these characteristics may occur.

The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.