

Productsheet

SYNTIX PRO IND 15W40 Ci-4SL

SYNTIX PRO IND 15W40 Ci-4SL

SYNTIX PRO IND 15W40 Ci-4SL is a high quality mineral oil developed to provide reliable performance in a wide range of heavy-duty diesel applications. This high-performance oil is recommended for all modern diesel engines of trucks, off-road equipment and other heavy-duty applications. It is suitable for low-emission diesel engines with EGR specifications, being the Euro II, III and several IV engines). This product exceeds current demanding requirements of many U.S. and European diesel engine manufacturers.

Essential benefits

- Provides a full engine protection
- Suitable for heavy-duty diesel applications

SPECIFICATIONS

MB 228.3	ACEA A3/B4-10
MAN M3275-1	CUMMINS CES 20076
VOLVO VDS-3	CUMMINS CES 20077
ACEA E7-08 Issue 2	CUMMINS CES 20078
API CI-4/SL	MACK EO-M PLUS
RENAULT RL D-2	MACK EO-N
CATERPILLAR ECF -1a	MTU Type 2
CATERPILLAR ECF -2	RENAULT RLD
MB 229.1	JASO DH-1
ALLISON C4	DEUTZ DQC-III-10
DETROIT DIESEL 93K215	GLOBAL DHD-1

TYPICAL VALUES

SYNTIX PRO IND 15W40 Ci-4SL	unit	value	method
Density at 15°C	kg/m ³	888	ASTM D4052
Viscosity at 40°C	mm ² /s	97	ASTM D445
Viscosity at 100°C	mm ² /s	13.8	ASTM D445
Viscosity index		144	ASTM D2270
B.N. (HClO ₄ method)	mg KOH/g	10.5	ASTM D2896
Pourpont	°C	-36	ASTM D6892
CCS viscosity at -20°C	mPa.s	6500	ASTM D5293
Sulfated Ash	Mass %	1.59	ASTM D874
Flash Point COC	°C	220	ASTM D92

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.