

Productsheet

SYNTIX PRO IND HI 22

SYNTIX PRO IND HI 22

SYNTIX PRO IND HI 22 is a mineral oil, specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is recommended for the hydraulic systems of the following types : Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco and Worthington. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

Essential benefits

- Provides an excellent protection against wear and oxidation
- Includes excellent anti-foam properties
- Provides an excellent viscosity stability

SPECIFICATIONS

AFNOR NF E 48-603 HM
AFNOR NF E 48-690
AFNOR NF E 48-691
DENISON HF-2
DIN 51524 Part 2

EATON VICKERS I-286-S
EATON VICKERS M-2950-S
ISO 11158, HM
ISO 6743-4, HM

TYPICAL VALUES

SYNTIX PRO IND HI 15	unit	value	method
Density at 15°C	kg/m ³	865	ASTM D4052
Viscosity at 40°C	mm ² /s	21.3	ASTM D445
Viscosity at 100°C	mm ² /s	4.4	ASTM D445
Viscosity index		117	ASTM D2270
Pourpont	°C	-30	ASTM D6892
Flash Point COC	°C	195	ASTM D92

Specification variations in these characteristics may occur.

The instructions of manufacturer must be regarded. Further informations to be available by Syntix Lubricants.