

Technical Data Sheet



Mag 10 Lightweight "Tyvek F" Hood M23LHF

The M23LHF is a lightweight, disposable respiratory protective full hood made from Dupont™ Tyvek® "F" material with a fitted clear PVC visor which can be used with a range of Martindale PAPRs or compressed air.

The hood material is stitched and all seams are taped and heat sealed for maximum integrity and fitted with a LDPE "slip ratchet" head harness with PVC sweatband. The hood also has adjustable crown strap for maximum comfort.

Filtered air is supplied to the user's breathing zone via the internal fabricated air duct hood and is sealed around the neck via the integral draw string to ensure the integrity of the user's breathing zone.

The hood is supplied complete with an air supply hose.

Mag 10 Lightweight "Tyvek F" Hood M23LHF

Specification	Visor size	250mm x 155mm
	Weight: Assembled with hose	1043g
	Hose only	217g
	Hose Length	830mm
	Head harness size	54-59cm
Materials	Hose	PVC with plastic spiral reinforcement
	Sweatband	PVC
	Hood	Dupont™ Tyvek® "F" material
	Visor	PVC
	Head harness	LDPE
<small>DuPont™ is a trademark or registered trademark of E.I. du Pont de Nemours and Company</small>		
Standard	Approved to	EN 12941 Class TH2/3P EN 1835 LDH3 EN14594 Class 3A
	Storage	
	The headpiece must be stored in a clean dry atmosphere within the temperature range - 5 °C to + 55 °C at R.H. < 90% in its original packaging. Ideal storage conditions are 5 °C to 35 °C R.H. < 60%. Transport in original packaging. If stored in correct conditions the product has a 5 year shelf life.	