

Interflon Fin 25 Additive

Engine oil additive for petrol, diesel and gas engines

Product description

Engine oil additive containing Interflon's MicPol® Technology. Suitable for enriching virtually all types of mineral and synthetic engine oils used in most engines operating on petrol, diesel, (LPG) and gas.

Reduces engine friction during start-up and operation and improves compression for more engine power, less wear and less engine noise. Makes engines start quicker, run smoother and reduces oil and fuel consumption.

Application

For use in petrol, diesel and (LPG) gas engines of cars, trucks, busses, motorbikes, agricultural and construction equipment, forklifts, lawn-mowers, power generators, piston compressors and many other types of vehicles and machines.

Advantages

- Reduces oil consumption and improves fuel economy
- Extends oil change life
- Gives more power and a smoother running engine
- Reduces wear
- Makes cold engines start-up easier

Instructions for use

Shake before use. Change oil and filters when the oil is in a bad condition. Add 2-4% (6% for heavily contaminated engines) after each oil change and let the motor run idle or go driving for at least 15 minutes.

Safety regulations

See safety data sheet.

Packaging

See our current article list.

Transport regulations

See safety data sheet.

Interflon Fin 25 Additive

Engine oil additive for petrol, diesel and gas engines

Technical data

Property	Result	Method
Composition	Mixture of mineral oils, additives and MicPol®.	
Colour	White	
Odour	Oily	
Density @ 20°C	0.93 g/cm ³	
Dynamic viscosity @ 20°C	1850 mPas	ASTM D2983
Particle size MicPol®	0.05-15 µm	
Lowest application temperature	-20°C	
Highest application temperature	150°C	
Suitable for filters	>20 µm	
Shelf life*	3 years	

* Shelf life of the product when stored at room temperature in the original and unopened packaging.

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information contained herein is subject to change without notice.

INTERFLON BV, P.O. Box 1070
NL-4700 BB Roosendaal, The Netherlands
Tel. + 31 (0) 165 55 39 11 / www.interflon.com

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.

Interflon®/MicPol® is a registered trademark of Interflon BV.