

# STANDARD GRADE APPLICATION TAPE WITH RELEASE LINER ADHESION TECHNOLOGY








## BACKING

A standard weight latex saturated paper designed for the protective masking of wide format digital graphics and large vinyl graphics.

## ADHESIVE

A very low tack natural rubber adhesive system designed for transferring large graphics and for short- or long-term protection of large digital prints. The stable adhesive will not build over time and will remove easily from the printed graphic upon removal of the premask. Not for exterior applications.

## PHYSICAL SPECIFICATIONS

Adhesive		Natural rubber
Colour		White/Translucent
Tape Thickness (PSTC-33)		102 - 115 µm
*Adhesion to Steel (PSTC-1)		7 - 9 N/100 mm
Tensile Strength (PSTC-31)		74 N/25 mm
Elongation		3 - 4 %
Tear Resistance		50 g

\* Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.

## R TAPE RELEASE LINER ADHESION (RLA<sup>™</sup>) PERFORMANCE FEATURES

R Tape Products upgraded with RLA technology have improved adhesion to paper or film release liners, yet maintain the specified adhesion level to the vinyl or printed graphic. R Tape RLA Premasks anchor themselves to the release liner for superior lay flat to prevent tunneling and edge curling of stacked or rolled graphics. Some R Tape RLA products significantly reduce the need for heat and vacuum process after lamination.

## APPLICATIONS

- Protective tape for large wide format digital graphics / PRINTED and UNPRINTED vinyl graphics.
- Application tape for large sized graphics.
- Application tape for stencil film.
- Provides easy, clean removal from large printed or vinyl surfaces.

**WARRANTY:** R Tape warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user store the material in the original boxes (out of direct sunlight) from our factory. We also recommend that our material be stored at 21°C with 50% relative humidity. R Tape only warrants our products to be free from defects in workmanship or defects in R Tape material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.



**RESPONSIVE. RELIABLE. RESOURCEFUL.**