LG FULL HD DISPLAY SM5KB SERIES 65SM5KB





Suitable for Offices, Restaurants and Retail 65" IPS Panel

FEATURES:

- Slim desing, WebOS platform with Built-in Wi-Fi
- Native Resolution: 1920 x 1080 (Full HD)
- Aspect Ratio: 16: 9
 Brightness: 450 cd/m²
 Contrast Ratio: 1,300: 1
- Portratit and Landscape orientation

- Viewing Angle (H x V): 178° x 178°



*LED LCD Monitors combine LCD screen with LED back light technology

www.lg.com.au

Technical Data 65SM5KB



PANEL

Screen Size
Panel Technology
Aspect Ratio
Native Resolution
Brightness
Contrast Ratio(Original)
Dynamic CR
Operating Hours
Viiewing Angle (H x V)
Orientation
Surface Treatment
Response Time

CONNECTIVITY

Input (Rear) Digital
Analogue
Audio
External Control
USB
SD Card
Wi-Fi / Bluetooth

Output (Rear) Digital
Audio
External Control

PHYSICAL SPECIFICATIONS

Bezel Width
Monitor Dimension (W x H x D)
Dimension with optional stand (W x H x D)
Carton Dimensions (W x H x D)
Weight (head)
Weight(head+stand)
Packed Weight
VESA™ Standard Mount Interface

SPECIAL FEATURES

Additional

ENVIRONMENT CONDITIONS

Operation Temperature Operation Humidity

POWER

Power Supply DPM Typical / Smart Energy Saving on Power Off Power Type

STANDARD (CERTIFICATION)

Safety EMC ErP/US EPA

MEDIA PLAYER COMPATIBILITY

External Media player Attachable

SOFTWARE COMPATIBILITY

SuperSign-w lite / SuperSign-c

ACCESSORIES

Included

Optional

Warranty

65" (164 cm) IPS

16:9

1920 x 1080 (Full HD)

450cd/m²

1,300 : 1 (Native) 4,000,000:1 24 Hrs

178° x 178°

Portrait and Landscape

Hard coating (3H)m Anit-glare treatment (Haze 1% Typ.)

10ms (G to G BW), 7.6ms (WOT)

HDMI (1, Support HDCP 2.2), DP (1), DVI-D (1)

RGB (1)

RGB / DVI (1), Speaker (10W x 2)

RS232C (1), RJ45 (1), IR (1), Pixel Sensor (1)

USB 3.0 (1)

SDHC / Full Size (1)

Dual Band (802.11n) / (802.15.1)

DP Out (1) Yes (1) RS232C (1)

11.9mm (T/R/L), 18mm (B) 1457mm x 838mm x 56.5mm 1457mm x 898mm x 220mm 1561mm x 951mm x 170mm 27.9kg 32.9kg

32.9kg 33.8kg 300mm x 300mm

Time, Tile Mode, Colour Settings, Languages, Internal Memory (4GB), DPM Select, File Play with USB, USB Cloning, Input Label, Smart Energy Saving, Built-in Speakers, SD Card Slot, Sync Mode

0 °C to 40 °C 10 % to 80 %

100-240V~, 50/60Hz 0.7W 125W / 85W 0.5W Built-In Power

UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC / C-tick N/A / Yes (Energy Star 6.0)

Yes (MP500 / MP700, KT-OPSA)

Yes / Yes

Remote Controller (including 2ea battery), Power Cable, QSG, RGB Cable, Regulation Book, Phono to RSC232C Gender, Memory Cover

Stand (ST-652T), Pixel Sensor (KT-SP0), Media Player, Wall Bracket (LSW230B), OPS Kit (KT-OPSA), VESA Adapter (AM-B220S), HD BaseT (EB-B100)

3 Years (Parts & Labour)

Disclaimer: All product specifications correct at time of printing. Specifications may change without prior notice.

